



Production & Headquarters
 No 188 BaoYuan 4th Road
 HuoXian Village JiangQiao Town
 JiaDing District
 Shanghai 201812
 P.R. China
 Tel: +86-21-69132230
 Fax: +86-21-69136303

European sales office
 Gentse Weg 203
 8792 Desselgem
 Belgium
 Tel: +32-56-774515
 Fax: +32-56-775995
 Markets covered: Europe
belgianoffice@chinafloors.com
chinaoffice@chinafloors.com

7. WHITE OAK NARROW STRIPS - SPECIFICATIONS

White oak 2 1/4 inch		Box dimensions Dimensions: 2210*260*80	# of boxes per layer: 4	
	Quantity / Carton	Quantity / Pallet	Quantity / 20ft	Quantity / 40ft
Sq Mt	2.01	105	1029.1	Overweight
Sq Ft	21.67	1127	11077.4	
Carton	-	52	512	
Pallet	-	-	10	
# of layers on pallet:	13	Weight/box:	27kg.	
Pallet unloaded size:	2225*1066*135	Pallet unloaded weight:	30kg.	
Pallet loaded size:	2225*1066*1175	Pallet loaded weight:	1434kg	
Weight of goods in:	20ft: 16784kg	40ft: Overweight		

White oak 3 1/4 inch		Box dimensions Dimensions: 2210*260*80	# of boxes per layer: 4	
	Quantity / Carton	Quantity / Pallet	Quantity / 20ft	Quantity / 40ft
Sq Mt	2.18	113	1116.2	Overweight
Sq Ft	23.47	1220	12202.0	
Carton	-	52	512	
Pallet	-	-	10	
# of layers on pallet:	13	Weight/box:	29 kg	
Pallet unloaded size:	2225*1066*135	Pallet unloaded weight:	30kg.	
Pallet loaded size:	2225*1066*1175	Pallet loaded weight:	kg	
Weight of goods in:	20ft: kg	40ft: Overweight		

White oak 3 1/4 inch		Box dimensions Dimensions: 1210*260*80	# of boxes per layer: 4	
	Quantity / Carton	Quantity / Pallet	Quantity / 20ft	Quantity / 40ft
Sq Mt	1.19	62	1227.0	Overweight
Sq Ft	12.80	666	13310.2	
Carton	-	52	1032	
Pallet	-	-	20	
# of layers on pallet:	13	Weight/box:	16kg.	
Pallet unloaded size:	1230*1066*135	Pallet unloaded weight:	23kg.	
Pallet loaded size:	1230*1066*1175	Pallet loaded weight:	855kg	
Weight of goods in:	20ft: 17100kg	40ft: Overweight		

Basic specs

Wood species	Structure	Install system	Grade	Length	Width	Thickness	Finish	Texture
European White oak	Solid	T&G	ABC-mix	Random (300-1500mm, 1-5ft, average≥700mm)	57.2mm. 2 1/4 inch	18mm. 3/4 inch	Premium UV Aluminum Oxide	Flat
European White oak	Solid	T&G	ABC-mix	Random (300-1500mm, 1-5ft, average≥700mm)	82.6mm. 3 1/4 inch	18mm. 3/4 inch	Premium UV Aluminum Oxide	Flat

Technical information

Wood information	Dimensions/structure	Finish	Coating:
Species: White oak Origin: Mainly Germany Small amounts from other EUR countries Grade: ABC-mix	Moisture: ≤10% Moisture control system for incoming wood: Logs are bought, cut and lumber is put in kiln for appr. 20 days - planks from kiln are checked: if moisture > 10%, planks go to balance room for 3-4 days until moisture level is ok	Gloss: 25% Colours: Natural, Harvest Oak, Butterscotch, Gunstock, Coffee, Savoy Testing: Resistance to staining: no visible change	UV treffert coating (Aluminum Oxide 7 layers)