



**Production & Headquarters**  
 No 188 BaoYuan 4th Road  
 HuoXian Village JiangQiao Town  
 JiaDing District  
 Shanghai 201812  
 P.R. China  
 Tel: +86-21-69132230  
 Fax: +86-21-69136303

**European sales office**  
 Gentse Weg 203  
 8792 Desselgem  
 Belgium  
 Tel: +32-56-774515  
 Fax: +32-56-775995  
 Markets covered: Europe  
 belgianoffice@chinafloors.com  
 chinaoffice@chinafloors.com

## 9. INDUSTRIAL FLOORING - SPECIFICATIONS

**Floor Dimensions: 160\*20\*10**

	Quantity / Carton	Quantity / Pallet	Quantity / 20ft	Quantity / 40ft
Sq Mt	2.30	18.43	1161.22	Overweight
Sq Ft	24.80	198.40	12499.33	
Carton	-	8	504	
Pallet	-	-	63	
# of layers on pallet:	2		<b>Weight/box:</b>	
Pallet unloaded size:	960*640*135		<b>Pallet unloaded weight:</b>	
Pallet loaded size:	960*640*585		<b>Pallet loaded weight:</b>	
Weight of goods in:	20ft:		40ft: Overweight	

### Basic specs

Wood species	Grade	Length	Width	Height	Finish	Texture
European White oak	ABC-mix	160mm 6 1/4inch	10mm 3/8inch	20mm 3/4inch	Unfinished	Flat
			20mm 3/4inch	10mm 3/8inch		
			16mm 3/5inch	16mm 3/5inch		

### Technical information

Wood information		s/structure	Chinafloors standards
<b>Species:</b>	White oak	Moisture: ≤10%	32pcs in a group 160mm is width 320mm is length
<b>Origin:</b>	Europe (Germany) Small amounts from other EUR countries	Moisture control system for incoming wood: Logs are bought, cut and lumber is put in kiln for appr. 20 days - planks from kiln are checked: if moisture > 10%, planks go to balance room for 3-4 days until moisture level is ok	1.less than 0.2mm gap between two little boards 2.height difference is 0.3mm 3.length difference is +/- 0.5mm 4.width difference is +/-0.5mm
<b>Grade:</b>	ABC-mix		