



**Production & Headquarters**  
 No 188 BaoYuan 4th Road  
 HuoXian Village JiangQiao Town  
 JiaDing District  
 Shanghai 201812  
 P.R. China  
 Tel: +86-21-69132230  
 Fax: +86-21-69136303

**European sales office**  
 Gentse Weg 203  
 8792 Desselgem  
 Belgium  
 Tel: +32-56-774515  
 Fax: +32-56-775995  
 Markets covered: Europe  
 belgianoffice@chinafloors.com  
 chinaoffice@chinafloors.com

## 4. ENGINEERED UV-Oil Treffert Collection - SPECIFICATIONS

Box: big Dimensions: 2210*260*80				
	Quantity / Carton	Quantity / Pallet	Quantity / 20ft	Quantity / 40ft
Sq Mt	3.30	158	1584.0	Overweight
Sq Ft	35.52	1705	17050.0	
Carton	-	48	480	
Pallet	-	-	10	
# of layers on pallet:	12	Weight/box:	25kg.	
Pallet unloaded size:	2225*1066*140	Pallet unloaded weight:	30kg.	
Pallet loaded size:	2225*1066*1110	Pallet loaded weight:	1230kg.	
Weight of goods in:	20ft: 12300kg.	40ft: Overweight		

Box: small Dimensions: 1210*260*80		Normal pallet (4 boxes per layer)		
	Quantity / Carton	Quantity / Pallet	Quantity / 20ft	Quantity / 40ft
Sq Mt	1.80	86	1728.0	Overweight
Sq Ft	19.38	930	18600.0	
Carton	-	48	960	
Pallet	-	-	20	
# of layers on pallet:	12	Weight/box:	14.6kg.	
Pallet unloaded size:	1230*1066*140	Pallet unloaded weight:	23kg.	
Pallet loaded size:	1230*1066*1100	Pallet loaded weight:	724kg.	
Weight of goods in:	20ft: 14480kg.	40ft: Overweight		

Box: small Dimensions: 1210*260*80		Europallet (3 boxes per layer)		
	Quantity / Carton	Quantity / Pallet	Quantity / 20ft	Quantity / 40ft
Sq Mt	1.80	65	1425.6	Overweight
Sq Ft	19.38	698	15345.0	
Carton	-	36	792	
Pallet	-	-	22	
# of layers on pallet:	12	Weight/box:	14.6kg.	
Pallet unloaded size:	1230*820*140	Pallet unloaded weight:	20kg.	
Pallet loaded size:	1230*820*1100	Pallet loaded weight:	546kg.	
Weight of goods in:	20ft: 12012kg.	40ft: Overweight		

### Basic specs

Wood species	Structure	Install system	Grade	Length	Width	Thickness	Finish	Texture
European White oak	Engineered Top veneer: 3mm. Base: poplar	Click	ABC-mix	Random (Big box:400-1500mm, 1.3*5ft, average≥700mm) Small box: 400-1200mm, 1.3*4ft, average≥600mm)	125mm. 4 7/8 inch	12mm. 1/2 inch	UV-Oil Treffert	Even

### Technical information

Wood information		Dimensions/structure		Testing:		Result	Standard	Finish	
Species:	White oak	# of layers:	3 base, 5 middle and 1 top layer	Glue:	Formaldehyde emission (mg/L):	0.3	E1: ≤ 1	Gloss level:	Standard 10%
Origin:	Europe (Germany) Small amounts from other EUR countries	Top veneer:	3mm. white oak		Water soak delamination test:	None	Sum of del. ≤ 1/3 of total sample L.	Colours:	Natural - Weathered - Light Grey - Autumn - Chocolate
Grade:	ABC-mix	Plywood:	poplar ( no exotic plywood)		Bending strength (MPa):	67.7	≥30	Finish:	UV-Oil Treffert coating
		Press:	3+5 layers of plywood: hot press Plywood + veneer: cold press		Bending Modulus of elasticity (MPa):	7452	≥4000		Refinishable
		Moisture:	≤10% (top veneer)						