



Production & Headquarters
 No 188 BaoYuan 4th Road
 HuoXian Village JiangQiao Town
 JiaDing District
 Shanghai 201812
 P.R. China
 Tel: +86-21-69132230
 Fax: +86-21-69136303

European sales office
 Gentse Weg 203
 8792 Desselgem
 Belgium
 Tel: +32-56-774515
 Fax: +32-56-775995
 Markets covered: Europe
belgianoffice@chinafloors.com
chinaoffice@chinafloors.com

8. ENGINEERED SPECIALS (108 MM WIDE) - SPECIFICATIONS

Box: big Dimensions: 2210*225*80				
	Quantity / Carton	Quantity / Pallet	Quantity / 20ft	Quantity / 40ft
Sq Mt	2.85	185.33	1853.28	Overweight
Sq Ft	30.69	1994.87	19948.71	
Carton	-	65	650	
Pallet	-	-	10	
# of layers on pallet:	13		Weight/box:	
Pallet unloaded size:	2225*1150*135		Pallet unloaded weight:	
Pallet loaded size:	2225*1150*1175		Pallet loaded weight:	
Weight of goods in:	20ft:		40ft: Overweight	

Basic specs

Wood species	Structure	Install system	Grade	Length	Width	Thickness	Finish	Texture
White oak	Engineered Top veneer: 3mm. Base: poplar/meranti	T&G	ABC-mix	Random (400-1500mm, 1.3*5ft, average ≥ 700mm)	108mm. 4 1/4 inch	12mm. 1/2 inch	PU	Brushed - Handscraped
							UV	Flat

Technical information

Wood information	Dimensions/structure	Testing:	Result	Standard	Finish
Species: White oak Origin: Europe (Germany) Small amounts from other EUR countries Grade: ABC-mix	# of layers: 3 base, 5 middle and 1 top layer Top veneer: 3mm. white oak Veneer layers are sawn Meranti or poplar Plywood: Meranti or poplar Press: 3+5 layers of plywood: hot press Plywood + veneer: cold press Moisture: ≤10% (top veneer)	Glue: Formaldehyde emission (mg/L): Water soak delamination test: Bending strength (MPa): Bending Modulus of elasticity (MPa): Resistance to staining:	0.3 None 67.7 7452 No visible change	E1: ≤ 1 Type 2 standard ≥30 ≥4000 No visible change	Gloss level: Standard PU 10% (5% tolerance) UV 25% (5% tolerance) Colours: PU: Wheat - Cognac - Coffee UV: Natural - Savoy - Coffee Finish: PU anti-scratch lacquer (4 roller and 1 curtain coating, applied 2x) UV: 7 layers (aluminum-oxide)